

SILVER GAL

Size 400g NET

IMPACT-A Silver Gal

IMPACT-A

Silver Gal



Anti Corrosion and Steel Paint

- Protects Iron and Steel against Rust and Corrosion
 - Zinc Rich
- Provides Excellent Long-Term Protection
- Touch Dry in 10 Minutes

400g NET

Impact-A Silver Gal is an anti corrosion Weld Through coating to provide long term protection for iron and steel against rust and corrosion.

Impact-A Silver Gal protects iron and steel against rust and corrosion. It is ideal for steel roofs, fences, gates or wrought iron, boats and marine equipment, air conditioning and heating systems. Impact-A Silver Gal provides excellent long-term protection and is ideally suited to coat any metal parts that require protection or touch ups to any galvanised parts.

Surface Protection

The correct surface preparation is critical. Both the paint and the metal must be in contact if a successful reaction is to take place. Wire brushing or mechanical sander must remove all loose materials until a firm base is established. The surface must be thoroughly cleaned and free from grease, oil, dirt, and other contaminants.

DO NOT use a Rust Converter.

Before Spraying

Cover nearby areas to protect from overspray. To ensure an even distribution of zinc throughout the paint it is important to shake the can for two minutes after mixing ball rattles and occasionally during use.

Spray Application

Adjust nozzle to the desired spray pattern. The horizontal setting used when spraying up and down. The vertical position when spraying across. Hold the can upright approximately 25cm from the surface. It is better to apply several light coats rather than one heavy coat.

Drying Time

Dries to touch in 10 minutes. Apply additional coats if required after 1 hours.

After Spraying

To clean nozzle and prevent blocking, turn the can upside down and press button until only gas escapes.

Over Coating

Impact-A Silver Gal does require a topcoat. Where a topcoat is desired the surface maybe be over coated with both Enamel and Acrylic paint systems.

Clean Up

Use mineral turps to remove any overspray.

Caution – Highly Flammable

Keep away from flame and heat. Keep in a cool place out of the sun. Do not puncture or incinerate can even when empty. Do not store above 50°C. Avoid breathing vapours or contact with skin or eyes.



IMPACT-A

